

TOWING TRACTOR

2.0-3.0Ton

New Product Release



TOWING TRACTOR 2.0-3.0 TON

1	Model		TD20	TD25	TD30	
2	Power type		Diesel	Diesel	Diesel	
3	Max.drawbar pull		KN	20	25	30
4	Max.towed weight at dry even concrete surface	With one trailer	Kg	26000	33000	39000
		With a train of trailers	Kg	39000	49000	59000
6	Max.travel speed	Forward	Km/h	29	26	26
7		Backward	Km/h	20	17	17
8	Max.gradeability (No load)		%	35	35	35
9	Overall length (with coupler)		mm	3150	3150	3150
10	Overall width		mm	1440	1440	1440
11	Overall height		mm	1450	1450	1450
12	Wheelbase		mm	1600	1600	1600
13	Front overhang		mm	650	650	650
14	Rear overhang (with coupler)		mm	900	900	900
15	Front tread		mm	1200	1200	1200
16	Rear tread		mm	1190	1190	1190
17	Min.turning radius (Outer)		mm	3250	3250	3250
18	Floor height		mm	460	460	460
19	Seat height		mm	940	940	940
20	Center height coupler		mm	304.8/405	304.8/405	304.8/405
21	Coupler length		mm	260	260	260
22	Min.ground clearance		mm	150	150	150
23	Tire size	Front		6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
		Rear axle		7.00-15-12PR	7.00-15-12PR	7.00-15-12PR
25	Truck weight (No load)		Kg	3700	3950	4300
26	weight distribution	Front axle	Kg	1270	1200	1250
		Rear axle	Kg	2430	2750	3050
28	Model			C240PKJ	4TNE98-BQFLC	B3.3-C65T3
29	Displacement		cc	2369	3319	3300
30	Rated output		Kw/rpm	35.4/2500	42.1/2300	48/2600
31	Rated torque		Nm/rpm	139/1800	196/1600	214/1600

