

TCF

FIRST OF ITS KIND NEW INNOVATIVE P-SERIES

3-3.5T LITHIUM BATTERY FORKLIFTS

CATL

309V HIGH-VOLTAGE
PLATFORM WITH
CATL BATTERIES



FAST CHARGING FULL
WITH ONLY 30 MINUTES
= 8 HOURS OF WORK



SUITABLE FOR EVERY
ENVIRONMENT -30 TO 60 °C,
HUMIDITY AND HIGH
ALTITUDE



GOODSENSE BALTIC OÜ

1.01	Model		P30H	P35H
1.02	Power Type		Electric	Electric
1.03	Rated Capacity	kg	3000	3500
1.04	Load Centre	mm	500	500
1.05	Service weight	kg	4520	4800


2.01	Tyre Type (Front/Rear)		Pneumatic	Pneumatic
2.02	Wheel number X = drive wheel (Front/Rear)		2X/2	2X/2
2.03	Tyre Size (Front)		28X9-15-14PR	28X9-15-14PR
2.04	Tyre Size (Rear)		6.50-10-10PR	6.50-10-10PR
2.05	Front Tread	mm	1000	1000
2.06	Rear Tread	mm	970	970
2.07	Wheelbase	mm	1700	1700

3.01	Fork Size (L x W x T)	mm	1070x125x45	1070x125x50
3.02	Mast Tilt Angle (F/R)	deg	6/12	6/12
3.03	Lift Height	mm	3000	3000
3.04	Mast Lowered Height	mm	2115	2150
3.05	Mast Extended Height	mm	4180	4180
3.06	Length to Face of Fork	mm	2741	2796
3.07	Overall Width	mm	1230	1230
3.08	Distance From Roof to Seat	mm	1020	1020
3.09	Front Overhang	mm	481	506
3.10	Rear Overhang	mm	575	610
3.11	Turning Radius (outside)	mm	2460	2495
3.12	Ground Clearance	mm	140	140

4.01	Max. Travel Speed (Full load/No load)	km/h	20/20	20/20
4.02	Lifting Speed (Full load/No load)	mm/s	520/530	430/440
4.03	Lowering Speed (Full load/No load)	mm/s	≤600 / ≥300	≤600 / ≥300
4.04	Max. Gradeability (Full load)	%	20	20

5.01	Battery(Type)		Li-Ion	Li-Ion
5.02	Battery(Voltage/Capacity)	V/Ah	309.12/96	309.12/96
5.03	Traction Motor Power, S2-60min	Kw	30	30
5.04	Lifting Motor Power, S3-15%	Kw	30	30
5.05	Controller		全交流	全交流
5.06	Operating Pressure	Mpa	18	18
5.07	Hydraulic Oil Tank Capacity	L	49	49

 Reti tee 6, Peetri, 75312 Harju maakond

 Tel. +372 56 983 983

 E-mail: info@goodsensebaltic.ee

 www.goodsensebaltic.ee

